

<https://dev.reachmee.com/api/public/v1/swagger>[Explore](#)

ReachMee API ^{1.0}

[Base URL: dev.reachmee.com/api/public/v1]

<https://dev.reachmee.com/api/public/v1/swagger>

The ReachMee REST API gives you programmatic access to most of your data stored in ReachMee. Using this API, you can easily export information about your projects, applications, candidates and system users. You can also use this API to update certain information in ReachMee, for example to keep your internal user directory in sync with ReachMee's user database.

Versioning

The ReachMee API uses url based versioning where the API version to use is specified as part of the request URL.

For a specific version, we guarantee that we will not remove parameters, response attributes or operations. However, we reserve the right to add fields and operations, so please ensure to design your client application accordingly to handle such scenarios.

Pagination

Responses that return an array of potentially large amounts of data will be split into different pages. In such cases `page_size` and `page` can be controlled by providing `page_size` and `page` parameters as part of the request. In the response for such requests, a `total_count` attribute is included to indicate total number of items in the collection and `next` and `previous` links are provided as shortcuts to next and previous pages where applicable.

Example:

```
{
  "total_count": 268,
  "previous": "/public/v1/projects?page=2",
  "next": "/public/v1/projects?page=4",
  "result": [...]
}
```

Localization

Some resources sent from the server may be localized in one of the languages supported by ReachMee. To specify which language to receive such information in, the standard HTTP Accept-Language header should be used. If no Accept-Language header is specified, or if an unsupported language is provided, the API will use the customer's default language instead.

[Terms of service](#)

<http://www.reachmee.com>

Authorize



hires



GET /hires List hires



Lists hires.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
updated_after string (query)	String representing the date in ISO 8601 format, 'YYYY-MM-DD' <input type="text" value="updated_after - String representing the date i"/>
updated_before string (query)	String representing the date in ISO 8601 format, 'YYYY-MM-DD' <input type="text" value="updated_before - String representing the date"/>
status string (query)	hire status <i>Available values</i> : NEW, DRAFT, READY, SENT, REVOKED, COMPLETED, REJECTED <input type="text" value="--"/>
page integer (query)	which page to fetch <i>Default value</i> : 1 <input type="text" value="1"/>
page_size integer (query)	size of the page to fetch <i>Default value</i> : 50 <input type="text" value="50"/>

Responses

Response content type

application/json

Code

Description

200

OK

Example Value **Model**

```
Gethires {
  hire_id           integer
  project_id        integer
  candidate_id      integer
  status            string
                   Status of hire
                   Enum:
                   Array [ 8 ]
  created           string
                   date completed
  updated           string
                   date created
  project_name      string
  name              string
  sign_in_order     boolean
  days_until_deleted string
  signing_parties   [...]
  signed_document   string
                   url to document
  attachments       [...]
  hire_details      {...}
}
```

Code	Description
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

GET **/hires/{id}** Get hire



Get hire.

Parameters

Try it out

Name	Description
------	-------------

id * required

string
(path)

Hire id

id - Hire id

Responses

Response content type

application/json

Code	Description
200	<div><div>OK</div><div>Example Value</div><div>Model</div><div><div><div>Gethires</div><div>{</div><div><div>hire_id</div><div>integer</div></div><div><div>project_id</div><div>integer</div></div><div><div>candidate_id</div><div>integer</div></div><div><div>status</div><div>string</div><div>Status of hire</div><div>Enum:</div><div>Array [8]</div></div><div><div>created</div><div>string</div><div>date completed</div></div><div><div>updated</div><div>string</div><div>date created</div></div><div><div>project_name</div><div>string</div></div><div><div>name</div><div>string</div></div><div><div>sign_in_order</div><div>boolean</div></div><div><div>days_until_deleted</div><div>string</div></div><div><div>signing_parties</div><div>[...]</div></div><div><div>signed_document</div><div>string</div><div>url to document</div></div><div><div>attachments</div><div>[...]</div></div><div><div>hire_details</div><div>{...}</div></div><div>}</div></div></div></div>

Code	Description
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

DELETE **/hires/{id}** Delete hire



Deletes hire from hire

Parameters

Try it out

Name	Description
------	-------------

id * required

string
(path)

Hire id

id - Hire id

Responses

Response content type

application/json

Code	Description
------	-------------

204	OK
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

GET /hires/{id}/contract Get hire contract



Get hire contract

Parameters

Try it out

Name	Description
------	-------------

Name	Description
------	-------------

id * required

string
(path)

Hire id

id - Hire id

Responses

Response content type

application/pdf

Code	Description
------	-------------

200

OK

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

404

Resource not found

GET

/hires/{id}/attachments/{attachment_id} Get hire attachment



Get hire attachment

Parameters

[Try it out](#)

Name

Description

id * requiredstring
(path)

Hire id

id - Hire id

attachment_id * requiredinteger
(path)

attachment_id

Responses

Response content type

[application/pdf](#)

Code

Description

200

OK

400

Incorrect request body or parameter

401

Unauthorized

Code	Description
403	Forbidden
404	Resource not found

users



GET **/users** Get users



Lists users in the system. Use the specified input parameters to limit the returned result.

Parameters

Try it out

Name	Description
------	-------------

user_name string (query)	user name
--------------------------------	-----------

user_name - user name

email string (query)	email
----------------------------	-------

email - email

Name	Description
external_org_unit_id string (query)	the external organization unit id <div>external_org_unit_id - the external organizati</div>
employee_number string (query)	Employment number of the user <div>employee_number - Employment number of 1</div>
page integer (query)	which page to fetch <i>Default value : 1</i> <div>1</div>
page_size integer (query)	size of the page to fetch <i>Default value : 50</i> <div>50</div>

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
200	OK
	Example Value Model
	<div><div>ApiUsersResponse</div><div><div><div>{</div><div>user_id</div><div>integer</div><div>the id of the user</div><div>user_name</div><div>string</div><div>the user name of the user</div><div>employee_number</div><div>string</div><div>the employee number of the user</div><div>first_name</div><div>string</div><div>the first name of the user</div><div>surname</div><div>string</div><div>the last name of the user</div><div>org_unit_id</div><div>string</div><div>ReachMee's internal organization unit id where the user belongs</div><div>external_org_unit_id</div><div>string</div><div>external organization unit id where the user belongs</div><div>last_login</div><div>string</div><div>the active/inactive status of the user</div><div>email_home</div><div>string</div><div>(DEPRECATED) the home email of the user</div><div>email_work</div><div>string</div><div>the work email of the user</div><div>telephone_1</div><div>string</div><div>the telephone 1 of the user</div><div>telephone_2</div><div>string</div><div>the telephone 2 of the user</div></div></div></div>

Code	telephone_2	string
		(DEPRECATED) the telephone 2 of the user
	telephone_3	string
		(DEPRECATED) the telephone 3 of the user
	date_removed	string
		date this use was inactivated
		}

400
Incorrect request body or parameter

401
Unauthorized

403
Forbidden

412
Precondition failed

POST **/users** Create user



Creates a new system user based on the supplied body parameters.

Parameters

Try it out

Name	Description
------	-------------

user * required

Name	Description
object (body)	Data for the user to be created.
	Example Value Model
	<div><div>ApiPostUser {</div><div><div>user_name*</div><div>string</div><div>the user name of the user</div></div><div><div>employee_number</div><div>string</div><div>the employee number of the user</div></div><div><div>login_type</div><div>string</div><div>default: INT</div><div>the login type for the user. EXT means SSO user.</div><div>Enum:</div><div>Array [2]</div></div><div><div>password</div><div>string</div><div>the password for the user</div></div><div><div>first_name*</div><div>string</div><div>the firstname of the user</div></div><div><div>surname*</div><div>string</div><div>the lastname of the user</div></div><div><div>email_work</div><div>string</div><div>the work email of the user</div></div><div><div>email_home</div><div>string</div><div>(DEPRECATED) the home email of the user</div></div><div><div>external_org_unit_id</div><div>string</div><div>external id for organization unit where this user belongs</div></div><div><div>telephone_1</div><div>string</div><div>telephone 1</div></div><div><div>telephone_2</div><div>string</div></div></div>

Name	telephone_1	string	(DEPRECATED) telephone 2
	telephone_3	string	(DEPRECATED) telephone 3
	}		

Responses

Response content type

application/json

Code	Description
201	Created
	Example Value Model
	0
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

Code	Description
409	User already exists in the given organization

GET /users/{id} Get user



Returns user specified by the id path parameter. Data includes role information.

Parameters

Try it out

Name	Description
------	-------------

id * required

integer(\$int64) Id of the user.
(path)

id - Id of the user.

Responses

Response content type application/json

Code	Description
------	-------------

200	OK
-----	----

Example Value Model

Code

ApiUserResponse

```
{
  user_id      integer
               the id of the user

  user_name    string
               the user name of the user

  employee_number string
               the employee number of the user

  first_name   string
               the first name of the user

  surname      string
               the last name of the user

  org_unit_id  string
               ReachMee's internal organization unit id where the user belongs

  external_org_unit_id string
               external organization unit id where the user belongs

  last_login   string
               the active/inactive status of the user

  email_home   string
               (DEPRECATED) the home email of the user

  email_work   string
               the work email of the user

  telephone_1  string
               the telephone 1 of the user

  telephone_2  string
               (DEPRECATED) the telephone 2 of the user

  telephone_3  string
               (DEPRECATED) the telephone 3 of the user

  data_removed string
```

Code		string
	date_removed	date this use was inactivated
	login_type	string
		the login type for the user. EXT means SSO user.
		Enum:
		Array [2]
	}	
400	Incorrect request body or parameter	
401	Unauthorized	
403	Forbidden	
404	Resource not found	
412	Precondition failed	

PATCH /users/{id} Update user



Updates user specified by the id path parameter according to the request body content. Only attributes specified in the body will be updated. Any other attributes will remain unchanged.

Parameters

[Try it out](#)

Name	Description
------	-------------

id * required

integer(\$int64)
(path) Id of the user.

id - Id of the user.

body * required

object
(body) Data to update the specified user with.

Example Value Model

```
{
  "user_name": "string",
  "employee_number": "string",
  "login_type": "INT",
  "password": "string",
  "first_name": "string",
  "surname": "string",
  "email_work": "string",
  "email_home": "string",
  "external_org_unit_id": "string",
  "telephone_1": "string",
  "telephone_2": "string",
  "telephone_3": "string"
}
```

Parameter content type

application/json

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
------	-------------

204	OK
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found
412	Precondition failed

GET **/users/{id}/roles** Get user roles



Returns roles for the user specified by the id path parameter.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
------	-------------

id * required

integer(\$int64) The user id to get roles for.
(path)

id - The user id to get roles for.

Accept-
Language
string
(header)

Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned loc

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
------	-------------

200

Roles for the specified user.

Example Value **Model**

```
ApiUserRoles  {
  role_name      string
                  name of the role
  description     string
                  description of the role
  role_id*       string
                  id of the role
  org_unit        {...}
}
```

401

Unauthorized

403

Forbidden

404

Resource not found

PUT **/users/{id}/roles** Assign role to user

Assigns the specified role to the user specified by the id path parameter.

Parameters

[Try it out](#)

Name	Description
------	-------------

id * requiredinteger(\$int64)
(path)

The id of the user.

id - The id of the user.

body * requiredobject
(body)

User role

Example Value Model

```
{
  "role_id": "string",
  "external_org_unit_id": "string"
}
```

Parameter content type

application/json

Responses

Response content type

application/json

Code	Description
------	-------------

204

Success

Code	Description
401	Unauthorized
403	Forbidden
404	Candidate not found

DELETE **/users/{id}/roles** Removes a role for a user



Removes the specified role from the user specified by id.

Parameters

Try it out

Name	Description
id * required integer(\$int64) (path)	The user id. <div>id - The user id.</div>
role_id * required string (query)	The id of the role to delete <div>role_id - The id of the role to delete</div>

Name	Description
external_org_unit_id string (query)	Identifies the organization unit where this role is assigned.

external_org_unit_id - Identifies the organizat

Responses

Response content type

application/json

Code	Description
204	Success
400	Bad request
401	Unauthorized
403	Forbidden
404	Resource not found

GET **/users/{id}/status** Get user status

Returns active/inactive status for the specified user.

Parameters

[Try it out](#)

Name	Description
------	-------------

id * required

integer(\$int64)
(path)
The user id.

id - The user id.

Responses

Response content type

application/json

Code	Description
------	-------------

200

Status information.

Example Value Model

```
{  
  "status": "active"  
}
```

401

Unauthorized

Code	Description
403	Forbidden
404	Candidate not found

PUT **/users/{id}/status** Set user status



Sets the active/inactive status of a user.

Parameters

Try it out

Name	Description
------	-------------

id * required

integer(\$int64)
(path)
The id of the user.

id - The id of the user.

Name	Description
------	-------------

body * required

object

Status to set for the specified user.

(body)

Example Value Model

```
{  
  "status": "active"  
}
```

Parameter content type

Responses

Response content type

Code	Description
------	-------------

204

OK

401

Unauthorized

403

Forbidden

Code	Description
404	Candidate not found

candidates



GET

/candidates/workflows

Get candidate workflows

Lists available workflows in the system.

Parameters

Try it out

No parameters

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
200	OK Example Value Model <pre>{ "name": "string", "description": "string" }</pre>
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found
412	Precondition failed

GET **/candidates/{id}** Get candidate



Gets candidate information

Parameters

Try it out

Name	Description
------	-------------

Accept-Language	Language for returned localized content. Valid input: sv-SE, en-UK, etc.
-----------------	--

string
(header)

Accept-Language - Language for returned loc

id	Id of candidate to get
----	------------------------

integer(\$int64)
(path)

id - Id of candidate to get

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
200	<div>OK</div> <div><div>Example Value</div><div>Model</div><pre>{ "address_care_of": "string", "address_city": "string", "address_postal_code": "string", "address_street": "string", "birth_day": "string", "birth_month": "string", "birth_year": "string", "candidate_id": 0, "country": "string", "date_created": "string", "email": "string", "first_name": "string", "image_link": "string", "is_employee": true, "last_name": "string", "linkedid_profile": "string", "personal_id": "string", "sex": "string", "sex_name": "string", "telephone_home": "string", "telephone_mobile": "string", "project_id": [{ "id": 0, "ad_id": 0, "current_status": "string", "date_policy_accepted": "string",</pre></div>
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden

Code	Description
404	Resource not found
412	Precondition failed

GET **/candidates/status/{status}** Get candidate



Gets candidate information

Parameters

Try it out

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc. Accept-Language - Language for returned loc
status * required string(\$int64) (path)	candidate status Available values : ACTIVE, REJECTED_BUT_INTERESTING, REJECTED, EMPLOYEE, APPLICATION_WITHDRAWN ACTIVE

Name	Description
since_date * required string (query)	Get candidates with changed status since <div>since_date - Get candidates with changed sta</div>
page_size integer (query)	Page size <div>page_size - Page size</div>
page integer (query)	Page number, starting at 1 <div>page - Page number, starting at 1</div>

Responses

Response content type

application/json

Code	Description
200	<div>OK</div> <div>Example Value Model</div> <div>ApiCandidatesResponse { address_care_of string Address c/o name address_city string</div>

Code

	City
address_postal_code	string Postal code
address_street	string Street address
birth_day	string Day in month, 01-31
birth_month	string Month in year, 01-12
birth_year	string Birthyear, e.g 1984
candidate_id	integer The id of the candidate
country	string Address country
date_created	string Creation date of candidate in the system
email	string Candidate email
first_name	string First name
image_link	string Link to candidate profile image
is_employee	boolean True if candidate is currently an employee
last_name	string Last name

Code		
	linkedid_profile	string Link to candidates Linkedin profile
	personal_id	string Personal id of candidate. Will show empty string if not filled in
	sex	string Numeric string representation of sex, '1' = female, '2' = male
	sex_name	string Name of sex
	telephone_home	string Telephone home
	telephone_mobile	string Telephone mobile
	project_id	[...]
	}	

400
Incorrect request body or parameter

401
Unauthorized

403
Forbidden

404
Resource not found

412
Precondition failed

GET **/candidates/workflows/{workflow}** Get candidate

Gets candidate information

Parameters[Try it out](#)

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc. Accept-Language - Language for returned loc
workflow * required string (path)	candidate workflows workflow - candidate workflows
since_date string (query)	Get candidates with changed workflow since since_date - Get candidates with changed wc
page_size integer (query)	Page size page_size - Page size

Name	Description
page integer (query)	Page number, starting at 1
<div>page - Page number, starting at 1</div>	

Responses

Response content type

application/json

Code	Description
200	<div>OK</div> <div>Example Value Model</div> <div><div>ApiCandidatesResponse {</div><div><div>address_care_of</div><div>string</div><div>Address c/o name</div></div><div><div>address_city</div><div>string</div><div>City</div></div><div><div>address_postal_code</div><div>string</div><div>Postal code</div></div><div><div>address_street</div><div>string</div><div>Street address</div></div><div><div>birth_day</div><div>string</div><div>Day in month, 01-31</div></div><div><div>birth_month</div><div>string</div></div></div>

Code

	Month in year, 01-12
birth_year	string Birthyear, e.g 1984
candidate_id	integer The id of the candidate
country	string Address country
date_created	string Creation date of candidate in the system
email	string Candidate email
first_name	string First name
image_link	string Link to candidate profile image
is_employee	boolean True if candidate is currently an employee
last_name	string Last name
linkedid_profile	string Link to candidates LinkedIn profile
personal_id	string Personal id of candidate. Will show empty string if not filled in
sex	string Numeric string representation of sex, '1' = female, '2' = male
sex_name	string Name of sex


```
Code
-----
    telephone_nome    string
                        Telephone home
    telephone_mobile   string
                        Telephone mobile
    project_id         [...]
  }
```

400
Incorrect request body or parameter

401
Unauthorized

403
Forbidden

404
Resource not found

412
Precondition failed

roles



GET **/roles** Get roles



Lists available roles in the system.

Parameters

Try it out

Name	Description
------	-------------

Accept-Language	Language for returned localized content. Valid input: sv-SE, en-UK, etc.
-----------------	--

string
(header)

Accept-Language - Language for returned localized content

Responses

Response content type

application/json

Code	Description
------	-------------

200

OK

Example Value **Model**

```
ApiRolesDto {
  role_id*      string
                The id of the role
  name          string
                The name of the role
  description   string
                The description of the role
  external_id   string
                The external id of the role
}
```

Code	Description
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found
412	Precondition failed

projects



GET **/projects** Get projects



Lists available projects in the system. Specify input parameters to limit the result. For most parameters, filtering is performed in like-based fashion, meaning that partial parameters can be supplied.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc. Accept-Language - Language for returned loc
id integer(\$int64) (query)	Id of project to get (performs like-based match) id - Id of project to get (performs like-based r
external_id string (query)	External id of project to get (performs like-based match). If empty string provided, projects without external id would be returned, if not provided, there will be no filter by external id. external_id - External id of project to get (perl
name string (query)	Project name (performs like-based match) name - Project name (performs like-based m
page_size integer (query)	Page size page_size - Page size
page integer (query)	Page number, starting at 1 page - Page number, starting at 1

Responses

Response content type

application/json

Code

Description

200

OK

Example Value **Model**

```
ApiProjectsResponse {
  next      string
            nullable: true
            link to next page

  previous  string
            nullable: true
            link to previous page

  total_count integer
            total number of items

  result    [...]
}
```

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

Code	Description
404	Resource not found
412	Precondition failed
500	Internal server error

POST **/projects** Create new project



Create a new project in ReachMee.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
project * required	
object	Data for the project to be created.
(body)	Example Value Model
<pre>ApiPostProject { name* string the name of the project external_id string external project code number_of_positions integer number of positions, default 1 description string project comment project_owner* string the owner of the project external_org_unit_id string external id for the organization unit }</pre>	

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
------	-------------

201

Created

Example Value Model

Unknown Type: application/json

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

500

Internal server error

GET **/projects/{id}** Get project

Get project information with orgunits by project id

Parameters[Try it out](#)

Name	Description
------	-------------

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned loc

id * required

integer(\$int64)
(path)
Id of the project to get

id - Id of the project to get

type
string
(query)

Regular json or PDF

type - Regular json or PDF

Responses

Response content type

application/pdf

Code	Description
------	-------------

200

OK

Example Value **Model**

```
ApiExtendProjectResponse {
  id                integer
  project code
  external id       string
```

Code

	external project code
name	string
	project name
description	string
	project comment
date_created	string
	date of project created
organization_unit	{...}
org_unit	{...}
form_of_employment	{...}
employment_degree	{...}
country	{...}
county	{...}
town_district	{...}
number_of_positions	integer
	number of positions at the project
position	{...}
area	{...}
orientation	{...}
ad_status	string
	advertisement status
	Enum:
	Array [4]
status	string
	project status
	Enum:
	Array [7]
job_ad_publishing_from_date	string
	advertisement publishing date
job_ad_publishing_to_date	string

```
      job_ad_publishing_to_date: string
      last day of advertisement publishing
    }
  }
  owner: {
    ...
  }
}
```

400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found
500	Internal server error

PATCH **/projects/{id}** Update project external id



Updates only external id of the project.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
------	-------------

id * required

integer(\$int64) project id
(path)

id - project id

body
object
(body)

New external id

Example Value **Model**

```
ApiPatchProject {  
  external_id      string  
  New external id. Should not be more than 60 symbols.  
}
```

Responses

Response content type **application/json**

Code	Description
------	-------------

200

OK

400

Incorrect request body or parameter

401

Unauthorized

Code	Description
403	Forbidden
404	Resource not found
500	Internal server error

GET **/projects/{projectid}/candidates** Get candidates in the project



Returns list of candidates.

Parameters

Try it out

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned loc

projectid * required

integer(\$int64)
(path)
id

projectid - id

Name	Description
page_size integer (query)	Number of projects at the page. Default - 25, max - 100. <div>page_size - Number of projects at the page. I</div>
page integer (query)	Page number, starting at 1 <div>page - Page number, starting at 1</div>
status string (query)	Status of candidate in the project <i>Available values</i> : ACTIVE, REJECTED_BUT_INTERESTING, REJECTED, EMPLOYEE, APPLICATION_WITHDRAWN <div>--</div>

Responses

Response content type

application/json

Code	Description
200	<div>OK</div> <div>Example Value Model</div> <div>ApiResponseCandidateResponse { address string </div>

Code

	candidate's address
birth_year	string
	candidate's birth_year
date_created	string
	date when candidate's profile was created
date_policy_accepted	string
	date when candidate agreed with the policy. Can be null if agreement wasn't given
date_updated	string
	date when candidate's profile was last updated
email	string
	candidate's email
first_name	string
	candidate's firstname
id	integer
	id of the candidate profile
mobile_phone	string
	candidate's mobile_phone number
phone	string
	candidate's phone number
sex	string
	male/female
source	string
	how did the candidate come to the system
status	string
	status of candidate in the project
	Enum:
	Array [5]
surname	string
	candidate's surname

Code	external_id	string
		External id, for example "diarienummer"
	}	
401	Unauthorized	
403	Forbidden	
404	Candidate not found	

POST **/projects/{projectid}/candidates** Create new candidate in a project



Create new candidate in a specified project. User with such email may already exist

Parameters

Try it out

Name

Description

projectid * required

integer(\$int64)
(path)

id of a project

projectid - id of a project

candidate * required

object
(body)

Data for the candidate to be created.

Name	Description
Example Value	Model
ApiPostCandidate	{
email*	string candidate's email
first_name*	string candidate's first name
last_name*	string candidate's last name
publishing_place_id*	integer id of publishing place from which candidate arrived
is_policy_accepted	boolean Is policy already accepted
ad_id*	integer id of advertisement that candidate came from
source	string URL of website that candidate came from
mobilephone	string candidate's mobile phone number
telephone	string candidate's telephone number
address	string candidate's address
careof	string candidate's address C/O (careof)
postal_code	string candidate's address postal code

Name	postal_city	string
		candidate's address postal city
	sex	string
		candidate's gender
		Enum:
		Array [2]
	birth_year	integer
		candidate's birth year
	birth_month	integer
		candidate's birth month
	birth_day	integer
		candidate's birth day
	ssn_last_four	integer
		last 4 numbers from candidate's SSN
	is_employee	boolean
		True if candidate is currently an employee
	linkedin_profile	string
		Link to candidates Linkedin profile
		}

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
------	-------------

201

Created

Example Value Model

121

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

500

Internal server error

GET

/projects/{projectid}/candidates/{candidateid} Get candidate in the project

Returns one candidate.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc. Accept-Language - Language for returned loc
projectid * required integer(\$int64) (path)	id projectid - id
candidateid * required integer(\$int64) (path)	id candidateid - id
page_size integer (query)	Number of projects at the page. Default - 25, max - 100. page_size - Number of projects at the page. I
page integer (query)	Page number, starting at 1 page - Page number, starting at 1

Responses

Response content type

application/json

Code	Description
200	<div>OK</div> <div>Example Value Model</div> <div><div><div>ApiProjectCandidateExResponse</div><div>{</div><div><div>address_care_of</div><div>string</div><div>Address c/o name</div></div><div><div>address_city</div><div>string</div><div>City</div></div><div><div>address_postal_code</div><div>string</div><div>Postal code</div></div><div><div>address_street</div><div>string</div><div>Street address</div></div><div><div>birth_day</div><div>string</div><div>Day in month, 01-31</div></div><div><div>birth_month</div><div>string</div><div>Month in year, 01-12</div></div><div><div>birth_year</div><div>string</div><div>Birthyear, e.g 1984</div></div><div><div>candidate_id</div><div>integer</div><div>The id of the candidate</div></div><div><div>country</div><div>string</div><div>Address country</div></div><div><div>date_created</div><div>string</div><div>Creation date of candidate in the system</div></div><div><div>date_policy_accepted</div><div>string</div></div></div></div>

Code

```

    date when candidate agreed with the policy. Can be null if agreement wasn't given

    email
      string
      Candidate email

    first_name
      string
      First name

    image_link
      string
      Link to candidate profile image

    is_employee
      boolean
      True if candidate is currently an employee

    last_name
      string
      Last name

    linkedin_profile
      string
      Link to candidates LinkedIn profile

    personal_id
      string
      Personal id of candidate. Will show empty string if not filled in

    sex
      string
      Numeric string representation of sex, '1' = female, '2' = male

    sex_name
      string
      Name of sex

    telephone_home
      string
      Telephone home

    telephone_mobile
      string
      Telephone mobile

    files
      {...}
  }

```

401

Unauthorized

Code	Description
403	Forbidden
404	Candidate not found

DELETE **/projects/{projectid}/candidates/{candidateid}** Deletes application from a project



Deletes application from a project.

Parameters

Try it out

Name	Description
projectid * required integer(\$int64) (path)	id of a project
candidateid * required integer(\$int64) (path)	id of a candidate

projectid - id of a project

candidateid - id of a candidate

Responses

Response content type

application/json

Code	Description
------	-------------

204	OK
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

POST `/projects/{projectid}/candidates/{candidateid}/documents` Upload candidate's document



Upload new candidate document in a specified project.

Parameters

Try it out

Name	Description
------	-------------

Name

Description

projectid * required

integer(\$int64)
(path)

id of a project

projectid - id of a project

candidateid * required

integer(\$int64)
(path)

id of a candidate

candidateid - id of a candidate

document * required

object
(body)

Data for the document to be created.

Example Value **Model**

```
ApiPostCandidateDocument {  
  base64*      string  
               Encoded file to base64 string  
  
  filename*    string  
               Filename including file extension.  
  
  type*        string  
               Type of candidate document, like CV, Photo of candidate, etc.  
               Enum:  
               Array [ 3 ]  
}
```

Responses

Response content type

application/json

Code	Description
------	-------------

201

Created

Example Value Model

Unknown Type: application/json

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

500

Internal server error

GET **/projects/{projectid}/ads** Get ads of the project

Returns list of ads as plain text.

Parameters[Try it out](#)

Name	Description
------	-------------

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned loc

projectid * required
integer(\$int64)
(path)

id

projectid - id

Responses

Response content type

application/json

Code	Description
200	OK
	Example Value Model

Code

Description

```
ApiProjectAdsResponse {
  project_id      integer
                  project id
  language        string
                  language of the ad
  date_created    string
                  date when ad was created
  date_updated    string
                  date when ad was last updated
  date_approved   string
                  date when ad was approved
  date_approve_requested string
                  date when ad's approve was last requested
  variant_name    string
                  name variant
  approved_status string
                  approved status
  publish_info    {...}
  header          string
                  ad's header
  text            string
                  text of the ad
  prefix_text     string
                  prefix text of the ad
  suffix_text     string
                  suffix text of the ad
```

Code	
401	Unauthorized
403	Forbidden
404	Project not found

GET **/projects/{projectid}/ads/{adid}** Download pdf-version of particular ad



Returns pdf-file.

Parameters

Try it out

Name	Description
------	-------------

adid * required

integer(\$int64)
(path)

ad id

adid - ad id

projectid * required

integer(\$int64)
(path)

project id

projectid - project id

Name	Description
------	-------------

type * required	
------------------------	--

string (query)	
-------------------	--

	Type of the document: pdf
--	---------------------------

	<div>type - Type of the document: pdf</div>
--	---

Accept-Language	
-----------------	--

string (header)	
--------------------	--

	Language for returned localized content. Valid input: sv-SE, en-UK, etc.
--	--

	<div>Accept-Language - Language for returned loc</div>
--	--

Responses	
-----------	--

	Response content type
--	-----------------------

	<div>application/pdf</div>
--	----------------------------

Code	Description
------	-------------

200	
-----	--

	OK
--	----

	Example Value Model
--	----------------------------

Code

Description

```
ApiProjectAdsResponse {
  project_id      integer
                  project id
  language        string
                  language of the ad
  date_created    string
                  date when ad was created
  date_updated    string
                  date when ad was last updated
  date_approved   string
                  date when ad was approved
  date_approve_requested string
                  date when ad's approve was last requested
  variant_name    string
                  name variant
  approved_status string
                  approved status
  publish_info    {...}
  header          string
                  ad's header
  text            string
                  text of the ad
  prefix_text     string
                  prefix text of the ad
  suffix_text     string
                  suffix text of the ad
```

Code	
401	Unauthorized
403	Forbidden
404	No such ad in this project.

organizations



GET **/orgunits** List organization units



Lists available organization units and their relationship.

Parameters

Try it out

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned loc

Name	Description
internal_id string (query)	Reachmee ID <div>internal_id - Reachmee ID</div>
external_id string (query)	External ID <div>external_id - External ID</div>
get_ancestors boolean (query)	Include ancestors from node, if any id is specified <div>--</div>

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
200	<p>OK</p> <p>Example Value Model</p> <pre>ApiOrgunitsResponse { org_unit_id integer id of organization unit external_org_unit_id string external id for organization unit name string name of organization unit status string 'active' or 'disabled' state of organization unit Enum: Array [2] children {...} }</pre>
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

POST **/orgunits** Create organization node

Creates a organization node based on external parent id.

Parameters[Try it out](#)

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned localized content

node * required

object
(body)

Data for the node to be created.

Example Value **Model**

```
ApiOrgunitsChildRequest {
  name string
  name of organization unit

  parent_external_org_unit_id string
  parent external id for organization unit

  external_org_unit_id string
  external id for organization unit

  vat_number string
  vat number

  review_person_email string
```

Name		reviewpersonemail
	postal_companyname	string
		postalcompanyname
	postal_country	string
		postalcountry
	postal_county	string
		postalcounty
	postal_address	string
		postaladdress
	postal_zipcode	string
		postalzipcode
	postal_city	string
		postalcity
	contact_name	string
		contactname
	contact_email	string
		contactemail
	contact_phone	string
		contactphone
	visit_country	string
		visitcountry
	visit_county	string
		visitcounty
	visit_address	string
		visitaddress
	visit_zipcode	string
		visitzipcode
	visit_city	string

Name

visitcity

}

Responses

Response content type

application/json

Code

Description

204

Created

Example Value Model

0

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

404

Resource not found

409

Org unit already exists in the given organization

PATCH **/orgunits/{id}** Update organization node

Updates an organization which id was provided.

Parameters[Try it out](#)

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned localized content

id * required string (path)	Id of the organization to update
--	----------------------------------

id - Id of the organization to update

node * required object (body)	Data for the node to be updated.
--	----------------------------------

Example Value **Model**

```
ApiOrgunitsChildRequest {
  name string
    name of organization unit
  parent_external_org_unit_id string
    parent external id for organization unit
  external_org_unit_id string
    external id for organization unit
```

external id for organization unit

Name

vat_number

string

vat number

review_person_email

string

reviewpersonemail

postal_companyname

string

postalcompanyname

postal_country

string

postalcountry

postal_county

string

postalcounty

postal_address

string

postaladdress

postal_zipcode

string

postalzipcode

postal_city

string

postalcity

contact_name

string

contactname

contact_email

string

contactemail

contact_phone

string

contactphone

visit_country

string

visitcountry

visit_county

string

visitcounty

visit_address

string

Name		visitaddress
	visit_zipcode	string
		visitzipcode
	visit_city	string
		visitcity
	}	

Responses

Response content type

application/json

Code	Description
------	-------------

204

Created

Example Value Model

0

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

Code	Description
404	Resource not found

GET **/orgunits/external_id/{external_id}** List organization unit



Lists organization unit and it's relationship.

Parameters

Try it out

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc. <div>Accept-Language - Language for returned loc</div>
external_id * required string (path)	External id of the organization <div>external_id - External id of the organization</div>

Responses

Response content type **application/json**

Code **Description**

200

OK

Example Value Model

```
{
  "org_unit_id": 0,
  "external_org_unit_id": "string",
  "name": "string",
  "status": "active",
  "children": {}
}
```

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

404

Resource not found

PATCH **/orgunits/external_id/{external_id}** Update organization node

Updates an organization which external id was provided.

Parameters[Try it out](#)

Name	Description
Accept-Language string (header)	Language for returned localized content. Valid input: sv-SE, en-UK, etc. Accept-Language - Language for returned loc
external_id * required string (path)	External id of the organization to update external_id - External id of the organization to

Name	Description
node * required object (body)	<p>Data for the node to be updated.</p> <p>Example Value Model</p> <pre>{ "name": "string", "parent_external_org_unit_id": "string", "external_org_unit_id": "string", "vat_number": "string", "review_person_email": "string", "postal_companyname": "string", "postal_country": "string", "postal_county": "string", "postal_address": "string", "postal_zipcode": "string", "postal_city": "string", "contact_name": "string", "contact_email": "string", "contact_phone": "string", "visit_country": "string", "visit_county": "string", "visit_address": "string", "visit_zipcode": "string", "visit_city": "string" }</pre> <p>Parameter content type</p> <div>application/json</div>

Responses

Response content type

application/json

Code	Description
------	-------------

Code	Description
------	-------------

204

Created

Example Value	Model
---------------	-------

0

400

Incorrect request body or parameter

401

Unauthorized

403

Forbidden

404

Resource not found

DELETE	/orgunits/external_id/{external_id}	Delete organization unit
--------	-------------------------------------	--------------------------



Deletes organization unit and it's relationship.

Parameters

Try it out

Name	Description
------	-------------

Name	Description
external_id * required string (path)	External id of the organization

external_id - External id of the organization

Responses

Response content type

application/json

Code	Description
204	OK
400	Incorrect request body or parameter
401	Unauthorized
403	Forbidden
404	Resource not found

ads



**GET** **/ads/{id}** Get ad

Returns an ad.

Parameters[Try it out](#)

Name	Description
------	-------------

id * requiredinteger(\$int64) ad id
(path)

id - ad id

Accept-Language
string
(header)

Language for returned localized content. Valid input: sv-SE, en-UK, etc.

Accept-Language - Language for returned loc

Responses

Response content type

application/json

Code	Description
------	-------------

200

OK

Example Value **Model**

Code

Description

```
ApiProjectAdsResponse {
  project_id      integer
                  project id

  language        string
                  language of the ad

  date_created    string
                  date when ad was created

  date_updated    string
                  date when ad was last updated

  date_approved   string
                  date when ad was approved

  date_approve_requested string
                  date when ad's approve was last requested

  variant_name    string
                  name variant

  approved_status string
                  approved status

  publish_info    {...}
  header          string
                  ad's header

  text            string
                  text of the ad

  prefix_text     string
                  prefix text of the ad

  suffix_text     string
                  suffix text of the ad
```


Code	
401	Unauthorized
403	Forbidden
404	No such ad in this project.

Models



Gethires

ApiStatus

ApiPostUser

ApiPatchUser

ApiUserResponse

ApiUsersResponse

ApiUserRoles

ApiPutUserRoles

ApiWorkflowsResponse

ApiCandidatesResponse

ApiRolesDto

ApiPatchProject

ApiPostProject

ApiPostCandidate

ApiPostCandidateDocument

ApiProjectsResponse

ApiExtendProjectResponse

ApiProjectCandidateResponse

ApiProjectAdsResponse

ApiProjectCandidateExResponse

ApiOrgunitsResponse

ApiOrgunitsChildRequest

INVALID {...}